

RECEIVED
CENTRAL FAX CENTER
NOV 13 2006

AMENDMENTS

Please amend the claims as follows:

1. (currently amended) An ultrasound transducer for ultrasound transmission and/or reception, the ultrasound transducer comprising:
at least one transducer element; and
a backing block adjacent the at least one transducer element, the backing block comprising a composite of first and second materials, the first material including a plurality of pockets filled with but not bonded to particles comprised of the second material;
wherein the pockets are less than 20 μ m along a maximum dimension.
2. (original) The transducer of Claim 1 wherein the first material comprises epoxy and the second material comprises silicone microspheres.
3. (cancelled)
4. (currently amended) The transducer of Claim ~~3~~ 1 wherein the pockets are less than 13 μ m along a maximum dimension.
5. (original) The transducer of Claim 1 wherein a density of the first material is within 10 percent of a same density as the second material.
6. (original) The transducer of Claim 1 wherein the first material comprises a first fraction of the volume of the backing block and the second material comprises a second volume fraction of the backing block, the first volume fraction being within 10 percent of a second volume fraction.
7. (original) The transducer of Claim 1 wherein the first material has a first acoustic impedance to ultrasound and the second material has a second acoustic impedance to ultrasound, the first acoustic impedance being within 10 percent of the second acoustic impedance.

8. (original) The transducer of Claim 1 wherein each of the plurality of pockets comprises a substantially spherical volume.
9. (original) The transducer of Claim 1 wherein the first material is incompatible with the second material.
10. (original) The transducer of Claim 1 wherein the pockets of the second material are enclosed within the first material, the second material unbound to the first material.
11. (original) The transducer of Claim 10 wherein the pockets of the second material are operable to generate friction against the first material in response to applied acoustic energy.
12. (original) The transducer of Claim 1 wherein the first material interconnects throughout the backing block, the backing block having a stiffness about the same as the first material.
13. (previously presented) An ultrasound transducer for ultrasound transmission or reception, the ultrasound transducer comprising:
 - at least one transducer element;
 - a backing block adjacent the at least one transducer element, the backing block comprising a composite of first and second materials, the second material incompatible with the first material wherein the second material is operable to generate friction with the first material in response to applied acoustic energy.
14. (original) The transducer of Claim 13 wherein the backing block includes pockets of the second material within the first material.
15. (original) The transducer of Claim 13 wherein the first and second materials comprise different polymers.

16. (original) The transducer of Claim 13 wherein the first material has a substantially different hardness but substantially the same acoustic impedance as the second material.
17. (cancelled)
18. (original) An ultrasound transducer for ultrasound transmission or reception, the ultrasound transducer comprising:
at least one transducer element;
a backing block adjacent the at least one transducer element, the backing block comprising a composite of solid silicone and a cured, nonsilicone resin.
19. (original) The transducer of Claim 18 wherein volumes of the silicone are enclosed within the resin.
20. (original) The transducer of Claim 18 wherein the backing block is substantially free of plasticizer.
21. (original) The transducer of Claim 18 wherein the composite has an acoustic impedance of about 1-2 MRayl.
- 22-28. (cancelled)